

PRODUCT SPECIFICATIONS:

PILE CONTENT:	80%Wool 20% Polypropylene
PILE WEIGHT:	1627 gm/m ² – 50 oz/yd ²
PILE HEIGHT:	10 mm
CARPET THICKNESS:	12 mm
MACHINE GAUGE:	3.175 mm - 1/8"
STITCH RATE:	As required to provide a carpet of total pile mass, pile height and machine gauge as specified.
WIDTH:	3.66 metres
PRIMARY BACK:	Heat Stabilised Woven Polypropylene
SECONDARY BACK:	Woven Jute
FIRE RATING:	AS/ISO 9239.1:2003 (A)
CRF VALUE:	4.1 kW/m ² (Conventional installation)
SMOKE DEVELOPMENT RATE:	224 % min (Conventional installation)
GRADING:	Residential Extra Heavy Duty Contract Medium Duty
ENVIRONMENTAL ACCREDITATION:	Achieves Level 3 Certification under the ACCS Environmental Classification Scheme
VOC EMISSIONS:	Meets ACCS Environmental Classification Criteria
WARRANTIES:	15 Year Limited Residential Wear Warranty 15 Year Limited Stain Resistance Warranty
TOLERANCE:	Manufactured to A.S. 1385 tolerances.
INSTALLATION:	To be laid in accordance with AS/NZS 2455.1:2007 Seam sealer must be applied to all seams (prior to joining).
SHADING: (Permanent Pile Reversal)	Cut pile carpets have a propensity to shade. This is not a manufacturing fault further information can be obtained from the Carpet Institute of Australia leaflet.
COUNTRY OF MANUFACTURE:	Australia