

TECHNICAL SPECIFICATIONS

Country of Origin:	Australia	Pile Weight:	813g/m ² (24oz)
Colours:	18 Standard	Backing:	Enviro Bac®
Yarn:	100% Nylon	Carpet Tiles & Planks Size:	250mm x 1000mm
Surface Texture:	Patterned Sculptured Loop Pile	Installation Method:	Direct Stick
Gauge:	47.2/10cm (1/12th Gauge)	Type:	Carpet Tiles and Planks
Total Product Thickness:	7 (+/- 1.0)mm	Units Per Box:	16.00
Pile Height:	4.5 (+/- 1.0)mm	m ² per box:	4

PERFORMANCE

Anti-Static:	(AATCC 134) <3.5KV at 21°C & 20% Relative Humidity
Flammability:	CRF 7.2kW/m ² (Direct Stick)~
Colourfast to light:	(ISO 105-B-02-1994) 5-6
Light Reflectance:	Available on Request
Stain Resistance:	Stain Warden®
Biocontaminant Control:	Bioshield® Antimicrobial Control
ACCS Rating:	Contract Extra Heavy Duty - 4 Star
Contract Guarantee:	15 Years Available on Request*
Smoke Value:	177% minutes (Direct Stick)

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council compliant for VOC emission rate limits
Product Transparency:	Declare Red List Free
Green Star:	Environmental Certification Scheme (ECS). Level 4 Maximum Points - Certificate #17123
Accreditation:	Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.

AVAILABILITY

Other Options:	Patterned Cut Pile, Textured Loop Pile
----------------	--



Declare.




Green Building Council Australia
Member

Spectrum



2700
SHIRAZ



2800
PLUM



3200
ZEST



6300
MELON



6400
TANGELO



6800
CRIMSON




7200
ASHEN



7400
COBBLESTONE



7600
CINDER



7900
GRAPHITE



8300
DENIM




8400
IMPERIAL




8500
INDIGO



8700
TEAL




8800
TURQUOISE



8900
EMERALD



9200
LICHEN



9800
KALE

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions.

ghcommercial.com

Spectrum



the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling. ~Test results and certificates are available on request.

*Guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.